Flash Check®
Jumbo Display Digital Pocket Probe Thermometer

Reduced tip for faster response time.

One piece ABS unibody and O-Ring sealed construction is the secret to superior strength and durability of the casing.

Adjustable calibration resistor (backside)

Smooth membrane surface and Touch-Pad™ efficiently seal against water, dirt, grease, and other intrusions.

72.5°F

Insert-molded steel Collar-Lock™

Convenient pocket Clip (backside)

Indicates °F or °C.
Flashes in display "HOLD" mode.

Magnet (backside)

Model 11000

Clear probe protection cap

This unique, next-generation, digital pocket probe thermometer is engineered to set the industry standard for accuracy, durability and readability. It is designed and constructed under exacting standards to meet and exceed the specifications required for commercial and industrial uses.

- Reduced tip probe thermometer provides 300% faster response time than conventional models
- Small-diameter probe ideal for measuring temperature of "thin masses" of food such as meat patties, Chicken and fish fillets per FDA Food Code 4-302.12 (B)
- Can be field calibrated
- Sealed unibody construction and RoHS-compliant
- IP56 waterproof & grease resistant

PATENT NO. 5,709,476

CE

Temperature Range	-40°F to 302°F (-40°C to 150°C)
Accuracy	±1°F (-4°F to 194°F), ±0.5°C (-20°C to 90°C); otherwise ±1.8°F (±1°C)
Resolution	0.1°F (0.1°C)
Display Size/Update	1.5" x 0.5" (38mm x 12.7mm)/Every 2 Seconds
Waterproof Rating	IP56
Probe Length and Tip Diameter	Stainless steel probe, 3.9 +/- 0.004 in. (99 +/- 0.1mm); Reduced probe tip 0.1 in. (2.3mm) diameter
Body/ Dimensions	Polycarbonate & ABS/ 6.98 in. (177.3mm) long
Calibration	Field calibratable. NIST traceable calibration certifiable.
Compliance Certificate	Manufacturers certificate of compliance available from DeltaTRAK
Battery	1.5V Button